



Franklin Fueling Systems

PIPING & CONTAINMENT SYSTEMS

EVOH LINED PIPEWORK

UPP™ semi-rigid pipework features an innovative clear inner lining made of natural EVOH resin to provide maximum pipe strength and superior vapour permeation and hydrocarbon barrier qualities.

HIGHLIGHTS

- UPP™ pipe is the first to receive an exceptional Class T1 temperature rating with its EN14125 approval, a true testament to its strength.
- Combining a PE100 High Density Polyethylene outer layer and an un-pigmented EVOH resin barrier layer enables a greater inner diameter, a potential increase in flow rates and a decrease in pressure loss.
- UPP™ pipe is rated for temperatures ranging from -40 °C to 50 °C.
- UPP™ pipework provides superior low permeation of 0g / m².



A Franklin Fueling Systems Brand

franklinfueling.com

3760 Marsh Rd. • Madison, WI 53718, USA

Tel: +1 608 838 8786 • Fax: +1 608 838 6433

Tel: USA & Canada +1 800 225 9787 • Tel: UK +44 (0)1473 243300

Tel: Mex 001 800 738 7610 • Tel: FR +33 (0)1 69 21 41 41 • Tel: CH +86 10 8565 4566

FFS-0507 03-16