

											
Module	Relay Module (TS-RLY)	10 Amp Relay Module (TS-10ARLY)	4-20 mA Module NIS (TS-420EXP)	AC Input Module (TS-ACI)	Input Output Module (TS-IO)	RS-485 Module (FMP-485IS)	UDP 24V Module (FMP-UDP24)	Probe Module (TS-PRB)	3-Wire Sensor Module (TS-3WSNS)	2-Wire Sensor Module (TS-2WSNS)	4-20 mA Module IS (TS-420IB)
Inputs	-	-	8	12	8 (3-240 VAC/DC)	4	12	12	8	12	8
Outputs	8	6	-	-	4 (4-20 mA)	-	-	-	-	-	-
EVO™ 600/6000 Compatibility	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
EVO™ 550/5000 Compatibility	✓	✓	✓	✓	✓	-	-	✓	✓	✓	✓
Franklin Electric Device Compatibility	SCM TS-SCCM WATER SEPARATOR 407985903 OVERFILL ALARM TS-RK	-	ELLD TS-LSU500E	-	-	MSH FMP-MSH	PROBES FMP-LL3-XXX FMP-LL3-XXX-I FMP-FLX-XXX TSP-LL2-XXX TSP-LL2-XXX-I SENSORS FMP-UHS FMP-ULS FMP-CDS-U FMP-DDS-U FMP-DDS-UD FMP-DIS-U FMP-DPS-U FMP-DTS-U FMP-EIS-U FMP-HIS-U FMP-HIS-XL-U TSP-DMS-XX	PROBES FMP-LL3-XXX FMP-LL3-XXX-I FMP-FLX-XXX TSP-LL2-XXX TSP-LL2-XXX-I SENSORS FMP-CDS-U FMP-DDS-U FMP-DDS-UD FMP-DIS-U FMP-DPS-U FMP-DTS-U FMP-EIS-U FMP-HIS-U FMP-HIS-XL-U TSP-DMS-XX	SENSORS FMP-DDS* FMP-DTS* FMP-EIS* FMP-HFS FMP-HFS2 FMP-HIS* FMP-HIS-XL* FMP-UHS* FMP-ULS* TSP-DVS TSP-HLS-XX TSP-HLS-XX/SS	SENSORS FMP-HFS FMP-HFS2 FMP-UHS* FMP-ULS* TSP-HLS-XX TSP-HLS-XX/SS	ELLD TS-LSU500 FMP-LSU500 SCM TS-SCCM SENSORS TS-VPS DEF RECIRCULATION FMP-TEM
Typical Application	Secondary containment control, submersible pump control, water separator control, and overfill alarm control.	Dispenser shutdown control	LS500 transducer pressure monitoring, third party 4-20mA device monitoring	Dispenser hook signal monitoring	Remote monitoring control, building monitoring system interfacing	Connecting to Multiplexing Sensor Hubs™	Liquid level monitoring, discriminating / non-discriminating liquid detection, corrosion control monitoring	Liquid level monitoring, discriminating / non-discriminating liquid detection, corrosion control monitoring,	Discriminating / non-discriminating liquid detection, overfill prevention	Non-discriminating liquid detection, overfill prevention	LS500 transducer pressure monitoring, vapor recovery monitoring, secondary containment monitoring, third party 4-20mA device monitoring

* EVO™ 600, EVO™ 6000, EVO™ 500, and EVO™ 5000, are backwards compatible with the TSP-XXX versions of the sensors.
NOTE: FMP-XXX-U sensors are not compatible with EVO™ 550/5000.