EagleFlex® E0-E85

E0-E85 Curb Pump Hose

- Recommended for use with Ethanol blends from E0 to E85
- Resistant to crushing and stands up to run-over
- Highly resistant to cuts, abrasions, sun and weather
- Flexibility of a softwall, durability of a hardwall
- Assures accurate readings at the pump
- Will not mark or scratch vehicle finishes
- Hose material is private branded and UL Listed to UL 330A and CAN/ULC-S612-99.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.



E0-E85 Wirebraid Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12ET04	3/4" E0-E85 4' Assembly Hose	1.7 (0.8)
CP12ET05	3/4" E0-E85 5' Assembly Hose	2.1 (1.0)
CP12ET06	3/4" E0-E85 6' Assembly Hose	2.5 (1.1)
CP12ET09	3/4" E0-E85 9' Assembly Hose	3.8 (1.7)
CP12ET10	3/4" E0-E85 10' Assembly Hose	4.2 (1.9)
CP12ET10X	3/4" E0-E85 10' Assembly Hose Bulk	4.2 (1.9)
CP12ET12	3/4" E0-E85 12' Assembly Hose	5.0 (2.3)
CP12ET12X	3/4" E0-E85 12' Assembly Hose Bulk	5.0 (2.3)
CP12ET14	3/4" E0-E85 14' Assembly Hose	5.9 (2.7)
CP12ET16	3/4" E0-E85 16' Assembly Hose	6.7 (3.0)
CP12ET20	3/4" E0-E85 20' Assembly Hose	8.4 (3.8)
CP12ET50X	3/4" E0-E85 50' Assembly Hose Bulk	21.0 (9.5)

Whip Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4" HOSES		
CP12ET.75	3/4" E85 9" Assembly Hose	0.86 (0.39)
CP12ET.66	3/4" E85 8" Assembly Hose	0.82 (0.37)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), wrap impression
Reinforcement	One wirebraid with full diameter grounding sheath
Temperature Range	-40°F to +180°F (-40°C to +82°C)

ISO 9001:2015 CERTIFIED COMPANY

c UL us

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EagleFlex® E0-E85

E0-E85 Curb Pump Hose

Dimensions and System Options

Available in these Sizes

ID	NOM OD		MAX WP		WEIGHT	
Size MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4" 19	1.10	28	150	1.03	0.42	0.63

Couplings

Permanent externally crimped zinc (L type).



Rev 2 1/25