# EagleFlex® Hardwall

## Premium Hardwall Gasoline Pump Hose

- Recommended anywhere a hardwall hose is required
- Recommended for all gasoline and gasoline/Ethanol blends at Ethanol levels designated as "gasohol" (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline
- Designed for durability, flexibility, and easy handling
- Highly resistant to cuts, abrasions, sun and weather
- Resists kinking and eliminates meter creep
- Improves ozone and abrasion resistance while providing increased life
- Improves draping and handling characteristics
- Will not mark or scratch vehicle finishes
- Hose material is private branded and UL Listed to UL 330 and CAN/ULC-S612-99
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.

*(See page two for coupling descriptions)*




SV TYPE

SV TYPE

R TYPE

L/MB TYPE

L/MB TYPE

LSV/LSVB TYPE

## Hardwall Hoses

| MODEL NO. | DESCRIPTION | SHIPPING WEIGHT LBS (KG) |
|---|---|---|
| **5/8" HOSES** | | |
| CP10HW09 | 5/8" Hardwall 9' Assembly Hose | 3.5 (1.6) |
| **3/4" HOSES** | | |
| CP12HWG08 | 3/4" Green Hardwall 8' Assembly Hose | 3.8 (1.7) |
| CP12HWG09 | 3/4" Green Hardwall 9' Assembly Hose | 4.2 (1.9) |
| CP12HWG10 | 3/4" Green Hardwall 10' Assembly Hose | 4.7 (2.1) |
| CP12HWG12SV | 3/4" Green Hardwall 12' Assembly Hose Swivel | 5.6 (2.5) |
| CP12HW09 | 3/4" Hardwall 9' Assembly Hose | 4.2 (1.9) |
| CP12HW09.5 | 3/4" Hardwall 9.5' Assembly Hose | 4.5 (2.0) |
| CP12HW09SV | 3/4" Hardwall 9' Assembly Hose Swivel | 4.2 (1.9) |
| CP12HW12 | 3/4" Hardwall 12' Assembly Hose | 5.6 (2.5) |
| CP12HW14 | 3/4" Hardwall 14' Assembly Hose | 6.6 (3.0) |
| CP12HW17 | 3/4" Hardwall 17' Assembly Hose | 8.0 (3.6) |
| CP12HW01L | 3/4" Hardwall 14' Assembly Hose | 6.6 (3.0) |
| CP12HWR01L | 3/4" Hardwall 14' Assembly Hose | 6.6 (3.0) |
| CP12HW01LSV | 3/4" Hardwall 14' Assembly Hose | 6.6 (3.0) |
| **1" HOSES** | | |
| CP16HW01 | 1" Hardwall 1' Assembly Hose | 0.64 (0.95) |
| CP16HW06 | 1" Hardwall 6' Assembly Hose | 3.8 (1.7) |
| CP16HW10 | 1" Hardwall 10' Assembly Hose | 6.4 (2.9) |
| CP16HW10X | 1" Hardwall 10' Assembly Hose Bulk | 6.4 (2.9) |
| CP16HW15 | 1" Hardwall 15' Assembly Hose | 9.6 (4.4) |
| CP16HW15X | 1" Hardwall 15' Assembly Hose Bulk | 9.6 (4.4) |
| CP16HW17 | 1" Hardwall 17' Assembly Hose | 10.9 (4.9) |
| CP16HW20X | 1" Hardwall 20' Assembly Hose Bulk | 12.8 (5.8) |

## Construction

| | |
|---|---|
| Tube | Black Nitrile |
| Cover | Black CPE (chlorinated polyethylene), wrap impression |
| Reinforcement | Multiple textile braids with dual static wire helix |
| Temperature Range | -40°F to +180°F (-40°C to +82°C) |
| Body | 3/4" Green Hardwall Available |

ISO 9001:2015 CERTIFIED COMPANY

c UL US

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# EagleFlex® Hardwall

**Premium Hardwall Gasoline Pump Hose**

## Dimensions and System Options

### Available in these Sizes

| ID | | NOM OD | | MAX WP | | WEIGHT | |
|---|---|---|---|---|---|---|---|
| Size | MM | IN | MM | PSI | MPA | LB/FT | KG/M |
| 5/8” | 16 | 1.03 | 26 | 150 | 1.03 | 0.39 | 0.58 |
| 3/4” | 19 | 1.17 | 30 | 150 | 1.03 | 0.47 | 0.70 |
| 1” | 25 | 1.45 | 37 | 150 | 1.03 | 0.64 | 0.95 |

### Couplings

Permanent internally expanded fixed chrome plated brass or external crimp zinc (L type).

Reattachable fixed and Reattachable swivel 3/4” and 1” male NPT. U L does not recognize field installation of reattachable fittings.




*Rev 11 2/22*