EagleFlex® Softwall

Softwall Gasoline Pump Hose

- A lightweight, flexible hose for use when a hardwall hose is inappropriate
- Recommended for all gasoline and gasoline/ Ethanol blends at Ethanol levels designated as “gasohol” (E15 maximum or less), diesel fuel and diesel fuel/biodiesel blends with nominal biodiesel concentrations up to 20% (B0-B20), kerosene and fuel oil (heating oil), leaded and unleaded gasoline
- Excellent strength without sacraficing flexibility.\
- Highly resistant to cuts, abrasions, sun and weather
- Smooth cover will not mark or scratch vehicle finishes.
- All curb pump hose assemblies are 100% pressure tested, inspected for electrical continuity and sample pull tested.



Softwall Hoses

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
3/4” HOSES		
CP12SW09	3/4” Softwall 9’ Assembly Hose	3.1 (1.4)
CP12SW10	3/4” Softwall 10’ Assembly Hose	3.4 (1.5)
CP12SW10X	3/4” Softwall 10’ Assembly Hose Bulk	3.4 (1.5)
CP12SW12	3/4” Softwall 12’ Assembly Hose	4.1 (1.9)
CP12SW14	3/4” Softwall 14’ Assembly Hose	4.8 (2.2)
CP12SW14X	3/4” Softwall 14’ Assembly Hose Bulk	4.8 (2.2)
CP12SW17	3/4” Softwall 17’ Assembly Hose	5.8 (2.6)
CP12SW20	3/4” Softwall 20’ Assembly Hose	6.8 (3.1)
CP12SW30	3/4” Softwall 30’ Assembly Hose	10.2 (4.6)
CP12SW50	3/4” Softwall 50’ Assembly Hose	17.0 (7.7)
CP12SW9.5	3/4” Softwall 9.5’ Assembly Hose	3.2 (1.5)
1” HOSES		
CP16SW10	1” Softwall 10’ Assembly Hose	4.7 (2.1)
CP16SW12	1” Softwall 12’ Assembly Hose	5.6 (2.5)
CP16SW14	1” Softwall 14’ Assembly Hose	6.6 (3.0)
CP16SW14X	1” Softwall 14’ Assembly Hose Bulk	6.6 (3.0)
CP16SW17	1” Softwall 17’ Assembly Hose	8.0 (3.6)
CP16SW20	1” Softwall 20’ Assembly Hose	9.4 (4.3)
CP16SW20X	1” Softwall 20’ Assembly Hose Bulk	9.4 (4.3)
CP16SW60	1” Softwall 60’ Assembly Hose	28.2 (12.8)

Construction

Tube	Black Nitrile
Cover	Black CPE (chlorinated polyethylene), smooth finish
Reinforcement	Multiple textile braids static wire
Temperature Range	-40˚F to +180˚F (-40˚C to +82˚C)

ISO 9001:2015 CERTIFIED COMPANY

c UL us

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

EagleFlex® Softwall

Softwall Gasoline Pump Hose

Dimensions and System Options

Available in these Sizes

ID		NOM OD		MAX WP		WEIGHT	
size	MM	IN	MM	PSI	MPA	LB/FT	KG/M
3/4”	19	1.10	28	150	1.03	0.34	0.51
1”	25	1.39	35	150	1.03	0.47	0.63

Couplings

Permanent internally expanded fixed chrome plated brass or external crimp zinc (L type).

Reattachable fixed and Reattachable swivel 3/4” and 1” male NPT. U L does not recognize field installation of reattachable fittings.



Rev 10 2/21